



**If you have any questions or concerns, please contact:
Jeremy Gulley (845) 887-4117 or blauser_4@yahoo.com**

ALL RULES HIGHLIGHTED IN RED ARE NEW OR UPDATED FOR 2023

Bone Stock V8, Compact & Bonestock Youth 80's and newer

GENERAL

1. NO Imps
NO Suicides
NO Hearses
NO Ambulances
NO Trucks or Truck Frames
Any question on car choice, please ask.
2. This class is open to any FWD or RWD V8, V6 or 4 cylinder car (other than what's listed).
3. NO WELDING. Two wires or chains per door. Two wire hold downs for hood. Two wire hold downs for trunks. No additional material may be added.
4. Move battery to passenger side floor board or front seat area. No milk crates, no zip ties, no zip screws can be used. Metal Battery box, BOLTED to the floor.
5. Move gas tank. (Make sure its secure, no zip Screws)
6. FACTORY shifter or simple threaded rod (NO AFTERMARKET)
7. Stock street tires – no ags, no skids. Any ply DOT street tires only - DOT marking must be visible. Small weld in centers will be allowed. Sidewall flaps will be allowed.
8. No aftermarket parts with the exception of a transmission cooler (fan or ice) will be allowed and must be secured.
9. Stock pedals
10. Any OEM car bumper can be used. Must be bolted on with factory bolts and remain in original location with factory sized bolts and factory number of bolts. You may weld the front bumper on with 4" of weld total per frame rail. FRONT AND REAR bumper must have 9 wire or chain in two locations thru **core support, (or) hood, (or) speaker deck, (or) roof only to hold them on. It may NOT go to the frame, DO NOT WELD.** Chain cannot be larger than 5/16" and no more than 3 strands of 9 wire. **Do not shorten frame.**

11. No suspension modifications
12. No body creasing
13. No tucking
14. No added bumper shocks
15. Headers will be allowed
16. You can weld your rear center to make it posi
17. Motor swaps allowed – weld the factory mounts in and that is it
18. One chain per motor mount. Must be bolted to factory frame hole. Max of 18” long.
19. No excessive mounts (max 8 inches of weld per mount)
20. No added steel
21. No cradles
22. Factory trans mount and cross-member
23. A 4-point cage will be allowed – for driver protection only! Anything in excess will be forced to cut or loaded at judge’s discretion.
24. Cage must be 5 inches from floor and firewall at any point.
25. Simple tank protector allowed, off the back bar only must be 8 inches from any sheet metal, keep it tight to the tank, do NOT ABUSE THIS rule or we will take it away.
26. DO NOT WELD...IF IT DID NOT COME OFF THE FACTORY FLOOR DO NOT DO IT.
OEM bolt on Only!!

PIT PASSES \$20

Alcoholic beverages are prohibited. Anyone caught in violation of the alcoholic beverages policy will be asked to leave the premises. All vehicles will be subject to search upon entry to the grounds. Anyone thought to be under the influence of alcohol or illegal substance will not be permitted on the grounds. Violations by any driver or crew member will result in disqualification and removal from the grounds.

© SPINNING WHEELS PRODUCTIONS

UPDATED February 3, 2023