



**If you have any questions or concerns, please contact:
Jeremy Gulley (845) 887-4117 or blausen_4@yahoo.com**

ALL RULES HIGHLIGHTED IN RED ARE NEW OR UPDATED FOR 2024

MOTOR SWAP V8

GENERAL

1. NO Imps
NO Suicides
NO Hearses
NO Ambulances
NO Trucks or Truck Frames
Any question on car choice, please ask.
2. Driver's door can be fully welded and may be skinned for driver's protection. You will be allowed a max of 4 spots per seam of 9 wire or 3/16" chain for hood, doors and trunk. Hood and trunk are considered to have two seams each (4 spots total on each). Each door is one seam (4 spots total for coupes, 8 spots total for sedans).
3. Move battery to passenger side floor board or front seat area. No milk crates, no zip ties, no zip screws can be used. Metal Battery box, BOLTED to the floor.
4. Move gas tank. (Make sure its secure, no zip Screws)
5. Any tire may be used
6. A transmission cooler (fan or ice) will be allowed and must be secured.
7. Aftermarket pedals and shifter will be allowed
8. Any OEM car bumper can be used, a factory replica bumper with a MAX 3/16" thickness, non-loaded (Catskill Fab, SMW, etc) or a homemade bumper may be used - 6" x 6" max tube, non-loaded, max 3/16" without point. Can be hard-nosed to the frame, single pass butt weld all the way around. No added metal. FRONT AND REAR bumper must have 9 wire or chain in two locations thru core support, (or) hood, (or) speaker deck, (or) roof only to hold them on. It may NOT go to the frame, DO NOT WELD. Chain cannot be larger than 5/16" and no more than 3 strands of 9 wire. Do not shorten frame.
9. Rear bumper must be a MINIMUM of 15" from the ground to the bottom of the bumper

10. Bolt in strut riser or a 3/16" MAX chain for the A-arm may be used. If using chain, it can only be welded one link in the center of the A-arm and one link on each end to the frame no further than 6" from A-arm on each side.
11. No body creasing
12. Quarter panels must remain vertical on all vehicles INCLUDING pre-rans. Trunk lid cannot be any closer than 8" from original trunk pan INCLUDING pre-rans.
13. No tucking
14. No added bumper shocks
15. Headers will be allowed
16. You can weld your rear center to make it posi
17. Motor swaps allowed – weld the factory mounts in and that is it
18. One chain per motor mount. Must be bolted to factory frame hole even with or in front of the A-Arm. Max of 18" long.
19. No excessive motor mounts (max 8 inches of weld per mount)
20. No added steel
21. No cradles
22. Factory trans mount and cross-member
23. Factory trailing arms must be used
24. A 4-point cage will be allowed – for driver protection only! Anything in excess will be forced to cut or loaded at judge's discretion.
25. Cage must be 5 inches from floor and firewall at any point.
26. Simple tank protector allowed, off the back bar only must be 8 inches from any sheet metal, keep it tight to the tank, do NOT ABUSE THIS rule or we will take it away.
27. DO NOT WELD...IF IT DID NOT COME OFF THE FACTORY FLOOR DO NOT DO IT.

PIT PASSES \$20

Alcoholic beverages are prohibited. Anyone caught in violation of the alcoholic beverages policy will be asked to leave the premises. All vehicles will be subject to search upon entry to the grounds. Anyone thought to be under the influence of alcohol or illegal substance will not be permitted on the grounds. Violations by any driver or crew member will result in disqualification and removal from the grounds.

© SPINNING WHEELS PRODUCTIONS

UPDATED JANUARY 23, 2024